

User Guide

Continuity tester



Table of Contents

1	Introduction	3
2	Continuity tester components	4
3	Safety instructions	4
4	Preparation	5
5	Operation	6
6	Standard compliance.	9
7	Warranty.	9

1 Introduction




Underfloor heating elements are strong but they can be damaged during installation & tiling. We recommend the Continuity tester to monitor your heating cables or mats during every installation step.

When connected to the underfloor heating mats, the alarm will sound when continuity is lost between the two heating conductors or if continuity develops between the ground wire or shield and one of the heating conductors.

If alarm sounds, stop work and check troubleshooting page in the User guide.

Product number: 088L0028



2 Continuity tester components

No.	Component	Pcs.	Designation
1		1	Continuity tester
2		2	AAA batteries
3		1	User Guide

3 Safety instructions

The safety instruction defines the type of tools and activity, which impacts using of the Continuity tester.

Verify that the mat or cable is not connected to a power source or live voltage!

Name	Tools
Screwdriver	
Utility knife	

4 Preparation

1. Open the battery compartment cover and insert two AAA size batteries (included). Make sure the batteries are installed correctly (see Figure 1).



Fig. 1

2. Replace the battery compartment cover and switch the unit "ON" (see Figure 2).



Fig. 2

3. The alarm should sound and the red light should be lit when there are no connections to an underfloor heating mat or loose cable. If these things do not occur, inspect the battery connection or replace the batteries.
4. During normal use (once the mat or cable is connected to the unit), the green light indicates that Continuity tester is monitoring the mat or cable for damage. Should the green light go out, replace the batteries before continuing work.

5 Operation

Make sure the mats and/or cables to be monitored are **not connected to a power source**.

Connect the system leads at beginning of the installation (see Figure 3).

The Continuity tester is designed to monitor the mats or cables individually. However, by making a temporary "series" connection of multiple mats or cables, it can monitor up to three products at one time.

1. FOR A SINGLE MAT OR LOOSE CABLE REEL: Strip the insulation around the tip of the cold cable and separate the sheath earth wire. Insert each lead wire of the cold cable into the L1 and L2 terminals with the earth wire inserted into the E terminal. Tighten the terminal screws onto the wires (as shown in Figure 3).



1. Cold lead (power cable)
2. Lead wires
3. Earth wire (Ground wire)
4. Switch

Fig. 3

2. **FOR UP TO TWO MATS OR CABLES:** Connect one lead wire (not the earth wire) from one mat or cable into the L1 terminal. Connect one lead wire (not the earth wire) from a DIFFERENT mat or cable into the L2 terminal. Now connect the re-maining lead wires so that the mats or cables are in “series” with one another. If this is not done properly, the Continuity tester may not correctly monitor the mats or cables.

Finally, connect all the earth wires from the mats or cables together to the E terminal (see Figure 4).




Fig. 4

3. Set the switch to the "ON" position.
4. A green light indicates Continuity tester is operating.
5. Place the Continuity tester where it can be seen and heard during the installation of the underfloor heating.
6. A red light and alarm indicate lead wires have come loose from terminals or that the underfloor heating elements have been damaged.

Please note: For added protection, we recommend all mats be tested with an actual OHM's meter for more specific readings.

6 Standard compliance

- ISO 1502:1996 ISO general-purpose metric screw threads – Gauges and gauging.
- ISO 13444:2012 Technical product documentation (TPD) – Dimensioning and indication of knurling.

7 Warranty

A 2-year product warranty is valid for:

- Continuity tester

Should you, against all expectations, experience a problem with your Danfoss product, you will find that Danfoss offers Danfoss warranty valid from the **date of purchase** on the following conditions: During the warranty period Danfoss shall offer a new comparable product or repair the product if the product is found to be faulty by reason of defective design, materials or workmanship. The repair or replacement.

The decision to either repair or replace will be solely at the discretion of Danfoss. Danfoss shall not be liable for any consequential or incidental damages including, but not limited to, damages to property or extra utility expenses. No extension of the warranty period following repairs undertaken is granted.

The warranty shall be valid only if the WARRANTY CERTIFICATE is completed correctly and in accordance

with the instructions, the fault is submitted to the installer or the seller without undue delay and proof of purchase is provided. Please note that the WARRANTY CERTIFICATE must be filled in, stamped and signed by the authorized installer performing the installation (Installation date must be indicated). After the installation is performed, store and keep the WARRANTY CERTIFICATE and purchase documents (invoice, receipt or similar) during the whole warranty period.

Danfoss warranty shall not cover any damage caused by incorrect conditions of use, incorrect installation or if installation has been carried out by non-authorized electricians. All work will be invoiced in full if Danfoss is required to inspect or repair faults that have arisen as a result of any of the above. The Danfoss warranty shall not extend to products which have not been paid in full. Danfoss will, at all times, provide a rapid and effective response to all complaints and inquiries from our customers.

The warranty explicitly excludes all claims exceeding the above conditions.

For full warranty text please use QR code



WARRANTY CERTIFICATE

The Danfoss warranty is granted to:

Address _____ Stamp _____

Purchase date _____

Serial number of the product _____

Product _____ Art. No. _____

*Connected output [W] _____

Installation Date & Signature _____ Connection Date & Signature _____

**Not mandatory*



Danfoss
Electric Heating

11655 Crossroads Circle
Baltimore, MD 21220
Tel: 1-888-Danfoss
www.heating.danfoss.us

Danfoss A/S
Climate Solutions • danfoss.com • +45 7488 2222

Any information, including, but not limited to information on selection of product, its application or use, product design, weight, dimensions, capacity or any other technical data in product manuals, catalogues, descriptions, advertisements, etc. and whether made available in writing, orally, electronically, online or via download, shall be considered informative, and is only binding if and to the extent, explicit reference is made in a quotation or order confirmation. Danfoss cannot accept any responsibility for possible errors in catalogues, brochures, videos and other material. Danfoss reserves the right to alter its products without notice. This also applies to products ordered but not delivered provided that such alterations can be made without changes to form, fit or function of the product.

▲ trademarks in this material are property of Danfoss A/S or Danfoss group companies. Danfoss and the Danfoss logo are trademarks of Danfoss A/S. ▲ rights reserved.