

## Ducted, Low Profile, 14.0kW

Ducted

White



### DIMENSIONS

|               |                |
|---------------|----------------|
| <b>Height</b> | <b>248 mm</b>  |
| <b>Width</b>  | <b>1500 mm</b> |
| <b>Depth</b>  | <b>700 mm</b>  |

### SPECIFICATIONS

#### Accessories

|                    |                 |
|--------------------|-----------------|
| Central controller | <b>Optional</b> |
| IR Controller      | <b>Optional</b> |

#### Capacity

|                       |               |
|-----------------------|---------------|
| Cooling capacity (kW) | <b>13.0kW</b> |
| Heating capacity (kW) | <b>15.0kW</b> |

#### Consumption

|     |             |
|-----|-------------|
| COP | <b>3.5</b>  |
| EER | <b>3.16</b> |

#### Features

|                              |                       |
|------------------------------|-----------------------|
| 24 Hour timer                | •                     |
| Auto restart                 | •                     |
| Blue fin coils               | •                     |
| Condensate pump              | •                     |
| DC inverter                  | <b>180° sine wave</b> |
| DRED (Demand Response) ready | •                     |
| MEPS approved                | •                     |
| Motor type                   | <b>DC motor</b>       |

|                             |               |
|-----------------------------|---------------|
| Self diagnostics            | •             |
| Sleep mode                  | •             |
| Standard controller         | <b>YR-E17</b> |
| Wi-Fi controller compatible | •             |

#### Installation

|                            |                    |
|----------------------------|--------------------|
| Corresponding outdoor unit | <b>1UH140P1ERG</b> |
|----------------------------|--------------------|

#### Performance

|                             |                       |
|-----------------------------|-----------------------|
| Airflow                     | <b>694l/s</b>         |
| DC inverter                 | <b>180° sine wave</b> |
| R410a refrigerant           | •                     |
| Self cleaning evaporator    | •                     |
| Sound power                 | <b>66dBA</b>          |
| Sound pressure              | <b>46dBA</b>          |
| Working temperature cooling | <b>-15 to 50 C</b>    |
| Working temperature heating | <b>-20 to 24 C</b>    |

#### Power Requirements

|                  |                   |
|------------------|-------------------|
| Power supply     | <b>220-240vac</b> |
| Supply frequency | <b>50Hz</b>       |

#### Product dimensions

|                     |                |
|---------------------|----------------|
| Depth               | <b>700 mm</b>  |
| Height              | <b>248 mm</b>  |
| Net weight          | <b>62kg mm</b> |
| Outdoor unit depth  | <b>370 mm</b>  |
| Outdoor unit height | <b>1350 mm</b> |
| Outdoor unit width  | <b>950 mm</b>  |
| Width               | <b>1500 mm</b> |

|                  |                |
|------------------|----------------|
| <b>Warranty</b>  |                |
| Parts and labour | <b>5 years</b> |

|     |       |
|-----|-------|
| SKU | 51493 |
|-----|-------|

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? 2020 Haier Inc. All rights reserved.

Other product downloads available at [haier.com](https://haier.com)

-  User Guide
-  Service & Warranty
-  Product Brochure
-  Installation Guide
-  Installation Guide (Outdoor Unit)
-  Installation Guide (WiFi)

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 0800 372273 W [www.haier.com](https://www.haier.com)