

Multi-Head Outdoor, 12kW

White



Part of our Super Match range, this outdoor unit can be paired with various indoor units for a complete multi-room air conditioning solution.

- Heating and cooling, with an operational range from -15°C to 46°C
- Outdoor unit connects to up to five indoor units
- High-efficiency DC fan motor
- Indoor unit options include cassette, slim ducted and high wall models

DIMENSIONS

Height	965 mm
Width	950 mm

Depth 370 mm

FEATURES & BENEFITS

Flexible combinations

The Super Match range offers a wide range of possible indoor unit and outdoor unit combinations, for a customised air conditioning solution for your space.

DC inverter technology

With 3D Direct Current (DC) inverter technology, Super Match air conditioning units are able to operate with a high level of energy efficiency, while delivering rapid heating and cooling as needed.

Anti-corrosion coating

The Blue Fin coating on the evaporator is hydrophilic for quick water drainage and resistance against corrosion.

R32 refrigerant

This Super Match outdoor unit uses a next-generation R32 refrigerant, which carries heat efficiently and has a lower Global Warming Potential than R410A.

Faster servicing

An easily accessible maintenance panel and service screen enable fast diagnostics.

Central controller

With an optional central controller, you can easily control individual or connected units, and schedule air conditioning to turn on and off automatically.

SPECIFICATIONS

Capacity

Cooling capacity (kW)	12.0kW
Heating capacity (kW)	12.0kW

Consumption

COP	4.10
EER	3.40

Features

Blue fin coils	•
Compressor type	Twin rotary
DC inverter	180° sine wave
DRED (Demand Response) ready	•
Inverter controlled compressor	•
MEPS approved	•
Refrigerant factory charge	2.5

Installation

Liquid line	5x 6.35
Maximum number indoor units	5
Maximum pipe run	100m
Suction line	3x 9.52 + 2x 12.7

Performance

Airflow	4200m ³ /h
DC inverter	180° sine wave
R32 Refrigerant	•
Sound power SWL (outdoor)	73dBA
Sound pressure SPL (outdoor)	58dBA
Working temperature cooling	-10°C to +46°C
Working temperature heating	-15°C to +24°C

Power Requirements

AMP draw	15.5A
Power phase	Single
Supply frequency	50Hz
Supply voltage	220-240V

Product dimensions

Depth	370 mm
Height	965 mm
Net weight	79kg mm
Width	950 mm

Warranty

Parts and labour	5 years
------------------	----------------

SKU	51630
-----	-------

Other product downloads available at haier.com

 [User Guide](#)

 [Installation Guide](#)

A PEACE OF MIND SALE**24 Hours 7 Days a Week Customer Support**T 0800 372273 **W**www.haier.com

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? 2020 Haier Inc. All rights reserved.