

VOYAGER XP 1400G

Accessories Guide



BSR idware GmbH
Jakob-Haringer-Str.3
A-5020 Salzburg
<https://www.bsr.at>
sales@bsr.at

Honeywell

MOUNTING HARDWARE AND STANDS



STND-19R02-002-4

Stand: gray, 19cm (7.5") stand height, rigid Voyager-like plastic pole, weighted tripod base, Voyager 1200 and 1400 cup



STND-23F03-002-4

Stand: gray, 23cm (9") stand height, flexible rod, weighted mid-sized universal base, Voyager 1200 and 1400 cup



HOLDER-004-U

Holder: desktop/wall mount, for Voyager 1200g and Voyager 1400g



STND-19R02-002-2

Stand: black, 19cm (7.5") stand height, rigid Voyager-like plastic pole, weighted tripod base, Voyager 1200 and 1400 cup



STND-19R02-002-0

Stand: light-gray, 19cm (7.5") stand height, rigid Voyager-like plastic pole, weighted tripod base, Voyager 1200 and 1400 cup



HOLDER-005-W

Holder: wall mount hook, for Voyager 1200g and Voyager 1400g

POWER SUPPLIERS



46-00525-6

Power Supply – NA Plug

Power Supply: NA plug, 1.0A @ 5.2V DC, 90-255V AC @ 50-60Hz, LV6, for use with Xenon and Voyager bases, or can be used to supply power to non-powered scanner serial cable connections.

46-00526

Power Supply – EU Plug

Power Supply: EU plug, 1.0A @ 5.2V DC, 90-255V AC @ 50-60Hz, for use with Xenon and Voyager bases, or can be used to supply power to non-powered scanner serial cable connections.

46-00528

Power Supply – AU Plug

Power Supply: AU plug, 1.0A @ 5.2V DC, 90-255V AC @ 50-60Hz, for use with Xenon and Voyager bases, or can be used to supply power to non-powered scanner serial cable connections.

46-00529

Power Supply – CN Plug

Power Supply: CN plug, 1.0A @ 5.2V DC, 90-255V AC @ 50-60Hz, for use with Xenon and Voyager bases, or can be used to supply power to non-powered scanner serial cable connections.

CABLES

CBL-500-150-S00

USB Cable

Cable: USB Type A, Host 5V Power Only, 150cm length, Straight, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-500-150-S00-05

USB Cable

Cable: USB Type A, Host 5V Power Only, 150cm length, Straight, No EAS, white, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-500-300-S00

USB Cable

Cable: USB Type A, Host 5V Power Only, 300cm length, Straight, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-500-300-S00-05

USB Cable

Cable: USB Type A, Host 5V Power Only, 300cm length, Straight, No EAS, white, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-500-300-C00

USB Cable

Cable: USB Type A, Host 5V Power Only, 300cm length, Coiled, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-500-400-C00

USB Cable

Cable: USB Type A, Host 5V Power Only, 400cm length, Coiled, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Product

CBL-500-500-C00

USB Cable

Cable: USB Type A, Host 5V Power Only, 500cm length, Coiled, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-800-300-S00

USB Cable

Cable: USB Type C, Host 5V Power Only, 300cm length, Straight, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-800-300-C00

USB Cable

Cable: USB Type C, Host 5V Power Only, 300cm length, Coiled, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-503-300-C00

USB Cable

Cable: USB 12V Locking, Host 5V Power Only, 300cm length, Coiled, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Product

CBL-503-300-S00

USB Cable

Cable: USB 12V Locking, Host 5V Power Only, 300cm length, Straight, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-020-300-C00

RS-232 Cable

Cable: RS232 (+5V signals) DB9 Femaie, Host 5V Power With Option For External 5V Power, 300cm length, Coiled, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-120-300-C00

RS-232 Cable

Cable: RS232 (+/-12V signals) DB9 Female, Host 5V Power With Option For External 5V Power, 300cm length, Coiled, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-720-300-C00

KBW Cable

Cable: KBW, black, PS2, 3m(9.8'), coiled, 5V external power with options for host power, w/o ferrite

CBL-MAG-300-S00

RS-232 Cable

Cable: RS232 (5V signals), Magellan Aux Port, black, 10 pin modular, 3m (9.8'), straight, external power with option for host scanner power

For more information

[automation.honeywell.com](https://www.honeywell.com/automation.honeywell.com)

Honeywell Industrial Automation

855 South Mint Street
Charlotte, NC 28202
800-582-4263
www.honeywell.com

Voyager XP 1400G Accessories Guide | Rev A | 08/25
© 2025 Honeywell International Inc.



BSR idware GmbH

Jakob-Haringer-Str.3

A-5020 Salzburg

<https://www.bsr.at>

sales@bsr.at

Honeywell