



05MM-WP70/77/78 Instruction Manual

05MM-WP70/77/78 Instruction Manual

THIS IS A TEMPLATE FOR YOUR 05MM-WP70/77/78 (115X55MM)

WARNINGS AND CAUTIONS

- To be installed by a suitably qualified installer.
- To be installed and used by appropriate electrical codes and regulations.
- If you are unsure about any part of these instructions, consult a qualified installer.

IMPORTANT INSTRUCTIONS

- Read and understand all instructions. Follow all warnings and instructions marked on the product.
- Do not use this product near water - e.g. near a bathtub, washbasin, sink, wet basement or near a swimming pool.
- Never push objects of any kind into this product through openings, as they may touch dangerous voltages.

Please ensure the mech inserts and accessories are of the correct style to match the mech bezel securely.

SAFETY INSTRUCTIONS

- Never install components during an electrical storm.
- Never install components in wet locations unless designed for such use.
- Never touch uninsulated wires or terminals unless the network interface wirings are disconnected.

Warning: To be installed by a licensed electrician or technician only. All power should be switched off before installation.

HOW TO INSTALL

1. **Warning:** To avoid fire, shock or death, turn off the power at the circuit breaker or fuse and test the power is off before continuing.
2. Choose the location for the WP7x. The installation requires mounting the WP7x using floating clips mounted on each side. Please select a wall location free from obstructions such as timber frames, metal wall straps, etc. Installing the WP7x near a stud or trimmer, please ensure there is at least 20mm clearance from the stud or trimmer edge so the floating clips can freely rotate into place. **Please ensure there is no wall point back to back if installed into an internal wall location, as this will affect the available wall depth.**
3. Cut out a hole in wall sheeting using the template provided as a guide. Check for obstructions in the wall cavity to ensure the WP7x will fit in its location.
4. Please install your chosen compatible mech (Clipsal® 2000 fitting) into the back of the wall plate and terminate cables as needed or run any direct cables through the brush or gland opening.
5. Push the wall plate into the cut-out until tight against the wall sheeting.
6. If the wall sheeting is of hard material, mark the stabilising fins' locations and make minor cuts until the plastic shroud is located firmly up against the wall sheeting.
7. Secure the wall plate in place using the preinstalled floating clips, one on each side.
8. Connect the WP7x cover

If installing more than one wall plate, ensure they are more than 50mm apart vertically or horizontally.

05MM-WP7x's designed for 70mm and 90mm wall cavities.

AU Technical Support
1800 237 425
matchmaster.com.au

NZ Technical Support
0800 237 425
matchmaster.co.nz

Australian design registration numbers: 202211247
New Zealand design registration numbers: 429684

Matchmaster Communications Pty Ltd accepts no responsibility for any loss or damage suffered by a person or their property as a result of the use, misuse, or failure of these goods. In the case of any defects within this product, Matchmaster Communications Pty Ltd liability would be limited to the replacement of this product.