

REVISIONS				
REV.	DATE	DESCRIPTION	DESIGNED	APPROVED
△				

71mm

105mm

Galaxy Tab S9+ Detachable Bluetooth Keyboard Cover User Manual

Notes: Please do not use the keyboard cover with the tablet for extended periods of time. The keyboard cover is designed to be used for a limited period of time. The keyboard cover is not intended to be used as a permanent input device. The keyboard cover is not intended to be used as a permanent input device.

System support
Android 12 or later

• User manual for iOS system connection

System support
iOS 12 or later

System support
Windows 10 or later

• User manual for Win 10 system connection

System support
Windows 10 or later

System support
Windows 10 or later

• FCC Statement

This device complies with the FCC Rules for Class B digital devices. The device does not create, use, or emit radio frequency energy. Therefore, it does not interfere with other devices, and it is not affected by other devices. The device is designed to be used in the United States and Canada. The device is not intended for use in other countries. The device is not intended for use in other countries.

• FCC Radio Frequency Statement

The device complies with the FCC Rules for Class B digital devices. The device does not create, use, or emit radio frequency energy. Therefore, it does not interfere with other devices, and it is not affected by other devices. The device is designed to be used in the United States and Canada. The device is not intended for use in other countries. The device is not intended for use in other countries.

• User manual for Android system connection

Notes: Please do not use the keyboard cover with the tablet for extended periods of time. The keyboard cover is designed to be used for a limited period of time. The keyboard cover is not intended to be used as a permanent input device. The keyboard cover is not intended to be used as a permanent input device.

System support
Android 12 or later

Product function

	Mini	Android	Windows	Macintosh
Connection	Yes	Yes	Yes	Yes
Keyboard	Yes	Yes	Yes	Yes
Mouse	Yes	Yes	Yes	Yes
Touchscreen	Yes	Yes	Yes	Yes
Bluetooth	Yes	Yes	Yes	Yes
USB	Yes	Yes	Yes	Yes
Wi-Fi	Yes	Yes	Yes	Yes
4G LTE	Yes	Yes	Yes	Yes
5G	Yes	Yes	Yes	Yes
6G	Yes	Yes	Yes	Yes
7G	Yes	Yes	Yes	Yes
8G	Yes	Yes	Yes	Yes
9G	Yes	Yes	Yes	Yes
10G	Yes	Yes	Yes	Yes
11G	Yes	Yes	Yes	Yes
12G	Yes	Yes	Yes	Yes
13G	Yes	Yes	Yes	Yes
14G	Yes	Yes	Yes	Yes
15G	Yes	Yes	Yes	Yes
16G	Yes	Yes	Yes	Yes
17G	Yes	Yes	Yes	Yes
18G	Yes	Yes	Yes	Yes
19G	Yes	Yes	Yes	Yes
20G	Yes	Yes	Yes	Yes
21G	Yes	Yes	Yes	Yes
22G	Yes	Yes	Yes	Yes
23G	Yes	Yes	Yes	Yes
24G	Yes	Yes	Yes	Yes
25G	Yes	Yes	Yes	Yes
26G	Yes	Yes	Yes	Yes
27G	Yes	Yes	Yes	Yes
28G	Yes	Yes	Yes	Yes
29G	Yes	Yes	Yes	Yes
30G	Yes	Yes	Yes	Yes
31G	Yes	Yes	Yes	Yes
32G	Yes	Yes	Yes	Yes
33G	Yes	Yes	Yes	Yes
34G	Yes	Yes	Yes	Yes
35G	Yes	Yes	Yes	Yes
36G	Yes	Yes	Yes	Yes
37G	Yes	Yes	Yes	Yes
38G	Yes	Yes	Yes	Yes
39G	Yes	Yes	Yes	Yes
40G	Yes	Yes	Yes	Yes
41G	Yes	Yes	Yes	Yes
42G	Yes	Yes	Yes	Yes
43G	Yes	Yes	Yes	Yes
44G	Yes	Yes	Yes	Yes
45G	Yes	Yes	Yes	Yes
46G	Yes	Yes	Yes	Yes
47G	Yes	Yes	Yes	Yes
48G	Yes	Yes	Yes	Yes
49G	Yes	Yes	Yes	Yes
50G	Yes	Yes	Yes	Yes
51G	Yes	Yes	Yes	Yes
52G	Yes	Yes	Yes	Yes
53G	Yes	Yes	Yes	Yes
54G	Yes	Yes	Yes	Yes
55G	Yes	Yes	Yes	Yes</

1. 관리 값은 반드시 「유해물질 금지 및 제한 관리 절차」의 규정에 부합해야 한다.
2. 친환경 관제 RoHS2.0+HF(무기물 제외)+PAHs15 표면 부품 시 필요

Material: 80g matte paper
Molding size: 71*105
Tolerance: +/-1mm

				108050262																																									
MODEL No.				PART No.				REMARK																																					
THIRD ANGLE PROJECTION UNIT : MM SIZE : A4				GENERAL TOLERANCE				MODEL No.:		SCALE:																																			
								108050351																																					
								PART NAME:																																					
								S9+ 分离式说明书																																					
APPROVED	CHECKED	DESIGNED	DIMENSIONS <table><tr><td>0-5</td><td>+0.00</td><td>-0.05</td><td>+0.10</td><td>+0.20</td><td>0°-30°</td><td>+0.10</td></tr><tr><td>6-10</td><td>+0.00</td><td>-0.10</td><td>+0.15</td><td>+0.20</td><td>30°-60°</td><td>+0.10</td></tr><tr><td>10-30</td><td>+0.00</td><td>-0.15</td><td>+0.20</td><td>+0.30</td><td>60°-90°</td><td>+0.10</td></tr><tr><td>30-100</td><td>+0.00</td><td>-0.20</td><td>+0.25</td><td>+0.30</td><td>90°-120°</td><td>+0.10</td></tr><tr><td>100+</td><td>+0.10</td><td>-0.20</td><td>+0.25</td><td>+0.30</td><td>120°-150°</td><td>+0.10</td></tr></table>				0-5	+0.00	-0.05	+0.10	+0.20	0°-30°	+0.10	6-10	+0.00	-0.10	+0.15	+0.20	30°-60°	+0.10	10-30	+0.00	-0.15	+0.20	+0.30	60°-90°	+0.10	30-100	+0.00	-0.20	+0.25	+0.30	90°-120°	+0.10	100+	+0.10	-0.20	+0.25	+0.30	120°-150°	+0.10	DRAWING No.:		REV:	
0-5	+0.00	-0.05	+0.10	+0.20	0°-30°	+0.10																																							
6-10	+0.00	-0.10	+0.15	+0.20	30°-60°	+0.10																																							
10-30	+0.00	-0.15	+0.20	+0.30	60°-90°	+0.10																																							
30-100	+0.00	-0.20	+0.25	+0.30	90°-120°	+0.10																																							
100+	+0.10	-0.20	+0.25	+0.30	120°-150°	+0.10																																							

Item	Mark	Description
1	CPK	Critical dimension for in-come quality control
2	EAI	Critical dimension for more tooling quality control